CHRYSO®Turbo F100

Hardening accelerating admixture

Chryso Concrete Solutions

DESCRIPTION

CHRYSO®Turbo F100 is a special formulation which provides the initial hydratation reaction of cements, particulary at low temperatures.

Setting is accelerated and mechanical strenght is developped rapidly. CHRYSO®Turbo F100 is low alkaline content.

FIELDS OF APPLICATION

- All cement types
- Cold weather concreting
- Ready-mix concrete
- Prestressed concrete
- Precast

INDICATIVE INFORMATION

Product Nature	liquid
Color	Translucent yellow
Lifetime	18 months

SPECIFICATIONS

CI ⁻ lons content	≤ 0,100 %
Equivalent Content NA ₂ O	≤ 2,70 %
Specific gravity	1,470 ± 0,020
рН	8,50 ± 1,00
Dry Extract (SYNAD - IFSTTAR)	51,50 % ± 1,50

NORMATIVE AND REGULATORY **INFORMATION**

- This product conforms to CE marking. The appropriate declaration can be found on our internet site.

METHOD OF USE

Dosage:

~ (

Dosage : from 1 to 5kg for 100kg of cement.

PRECAUTIONS

- Do not mix with acid products.
- Do not store in tin containers.
- Protect from frost.

SAFETY

Prior to any use, please read carefully the Material Safety Data Sheets.



he information contained in this document is given to the best of our knowledge and is the result of extensive and controlled testing. However, it cannot under any circumstances be considered as a warranty involving our liability in the case of misuse. Tests should be con ducted before the product is used to ensure that the methods and conditions of use of the product are satisfactory. Our specialists remain at the disposal of customers if they require help with the application of the product for their specific needs. www.chryso.se CHRYSO Nordic AB – Färgvägen 8 SE-443 61 STENKULLEN Tél.:+46(0)31-352 50 80 e-mail:info@chryso.se

P.1/1

